



KWIKbond

Latex Additive

PRODUCT OVERVIEW

KWIKbond Bonding Liquid is a latex additive that when used as a total replacement of water in tile adhesive mixes, improves the adhesive strength, flexibility, and water resistance of dry mortar tile adhesives and grouts.

FEATURES

[Datasheet](#)

- ✓ Improves Strength
- ✓ Water -Resistance
- ✓ Drying Time 4-8 HR
- ✓ Chemical-Resistant
- ✓ Strong Adhesion
- ✓ Durability and Flexibility

**Suitable for high traffic and temperature variations*

TECHNICAL DATA

PROPERTY

Colour	Milky White
Drying Time	4-8 hrs
Touch Dry	2-3 hrs
Curing Time	24 – 48 hrs
Coverage	1 L per 5m2 with block brush on fully cured substrate
Wet Film Build	1.4 – 2 mm
Shelf Life (appropriate storage)	6 – 12 months – sealed container
Packaging	5Lt plastic jerry can, 20Lt plastic bucket with pourer insert



SURFACE PREP

To be used with gypsum and cement plasters, mortars, and renders.



Substrates must be sound, clean, dust-free, and free from all traces of oil, curing compound, gypsum, paint, or laitance.



All varnish, sealers, polish, and previous coatings must be removed before priming occurs.

CURING

For best results, make sure your surfaces are properly cured:

NEW CONCRETE	✓ Let it cure for 6 weeks
NEW SCREED	✓ Let it cure for 4 weeks
NEW BRICKWORK	✓ Let it cure for 4 weeks
NEW RENDER	✓ Let it cure for 2 weeks

IMPORTANT NOTICE

KWIKtile believes the information provided is accurate but does not guarantee its completeness. Always test products to ensure suitability for your intended use. Users assume all risks and liabilities during testing and use. In special cases, seek professional advice. KWIKtile's only obligation is to replace any product proven defective in material.

KWIKtile is not liable for any injury, loss, or damage, direct or consequential, from the use or inability to use the product. Except as stated above, all products and samples are provided without warranties, express or implied. KWIKtile reserves the right to update this datasheet.

For the latest version contact:

KWIKtile Technical Support
info@kwiktile.co.za or **012 804 8337**

STORAGE

Store in dry, internal conditions in an undamaged sealed container.

SHELF LIFE

Shelf life is **12 months** from the date of manufacture.

SAFETY

Wear rubber gloves as tile adhesive may cause skin irritation. Always work in a well-ventilated space. Wear protective eyewear and a dust mask. Keep out of reach of children. Do not ingest. Dispose of responsibly, adhering to municipal regulations.

QUALITY

KWIKtile products are free from manufacturing defects and fit for design purposes, subject to proper use and good workmanship.

APPLICATION

①



KWIKbond BONDING LIQUID, is to be used as a replacement for the water component in our KWIKtile & KWIKgrout adhesive range.

②




Product containing KWIKbond BONDING LIQUID should be mixed to a smooth lump-free paste.

③



Mix should be allowed to stand for 5 minutes and then mixed again before use.

④



KWIKbond BONDING LIQUID is an additive for tile adhesives, screeds, and cement mortars, ideal for wet, humid, and high-traffic areas like bathrooms and kitchens.

⑤



It aids in areas that are exposed to thermal stresses from temperature extremes or persistent temperature changes (outdoor areas).