



KWIKtile

Siyakha Nawe



KWIKflex

High-Bond Flexible Adhesive

PRODUCT OVERVIEW

KWIKflex is a ready-to-use, high-bond, flexible adhesive for fixing ceramic tiles to horizontal and vertical surfaces without slumping. It can also bond cornices, wood, polystyrene, and concrete, and be used as a joint sealant and gap filler.

[Datasheet](#)

FEATURES

- ✓ Ceramic Tiles 24HR SET
- ✓ Cures After 1HR
- ✓ Ready Mix Tile Adhesive
- ✓ Large and Small Tile compatible
- ✓ General-Purpose adhesive
- ✓ Wood, Polystyrene and Corning

ADVANTAGES

- ✓ Quick Curing
- ✓ Easy and ready to use
- ✓ Non-Slump
- ✓ High bond strength
- ✓ Water Resistant (breathable)
- ✓ Versatility and Durability
- ✓ Paintable and Neutral colour

TECHNICAL DATA

PROPERTY

WITH WATER

Appearance

Paste

Components

Single Pack

Coverage

1 m²/kg depending on substrate porosity

Application

Notch Trowel

Cure Time

1 hour touch, 24 hours hard

Compressive Strength

20 mpa

Bond Strength

>1.5 mpa

Shelf Life


6 months

Packaging


2 kg, 5kg Buckets




SURFACE PREP



① Surfaces to be bonded must be clean and free of dust and grease.



② Ensure the substrate is as even and level as possible.



③ Painted surfaces, timber, fibre, and gypsum surfaces should be chipped 80% of surface area.



④ Wood and chip-board, when used in high moisture areas, should be primed with KWIK-Prime for good bonding.

CURING

For best results, make sure your surfaces are properly cured:

NEW CONCRETE

✓ Let it cure for **6 weeks**

NEW SCREED

✓ Let it cure for **4 weeks**


NEW BRICKWORK

✓ Let it cure for **4 weeks**


NEW RENDER

✓ Let it cure for **2 weeks**


APPLICATION




① Superflex is applied by notched trowel 6mm x 6mm. For larger or heavier tiles, use an 8 -10mm notched trowel.



② Firmly bed tiles into wet adhesive, pressing on all corners and center to ensure full contact.



③ Avoid slumping, which may result from uneven substrates. Apply tiles quickly to prevent surface drying of the adhesive.



④ On timber or flexible surfaces, allow for joint movement.



⑤ Do not disturb bonded items for at least 24 hours to ensure proper curing.



⑥ Clean tools with water immediately after use; use xylene if adhesive has dried.

GROUTING

Allow 24 hours before grouting. Use KWIKtile Grout as per instructions.

STORAGE

Store in dry, internal conditions between 10°C and

SHELF LIFE

Shelf life is **12 months** from the date of manufacture.

SAFETY

Do not ingest. Use only as directed. Keep out of reach of children. Wear protective gloves and goggles. Use a suitable dust mask when mixing. Work in a well-ventilated area.

WARRANTY

KWIKtile products are free from manufacturing defects and fit for design purposes, subject to proper use and good workmanship.

MOVEMENT JOINTS

- ✓ **Max 5m** centers for interior & wall applications.
- ✓ **Max 3m** centers for exterior applications.
- ✓ Place joints around perimeters, in corners, and over structural joints.
- ✓ Fill with suitable silicone and polyurethane joint sealant.

IMPORTANT NOTICE

KWIKtile believes the information provided is accurate but does not guarantee its completeness. Always test products to ensure suitability for your intended use. Users assume all risks and liabilities during testing and use. In special cases, seek professional advice. KWIKtile's only obligation is to replace any product proven defective in material.

KWIKtile is not liable for any injury, loss, or damage, direct or consequential, from the use or inability to use the product. Except as stated above, all products and samples are provided without warranties, express or implied. KWIKtile reserves the right to update this datasheet.

For the latest version contact:

KWIKtile Technical Support
info@kwiktile.co.za or 012 804 8337